

SecurActive NSS-10

Network and Security Surveillance Appliance



SecurActive NSS Solution

SecurActive NSS is a network and security surveillance appliance based on an innovative analysis engine. It captures network traffic and analyzes it, making the understanding of network activity easier.

With a graphic interface that is both intuitive and simple to use, SecurActive NSS provides a panel display which shows the type of traffic that flows through the network, detecting network anomalies and risks such as attacks, incoherent traffic, illegitimate traffic, threshold limits, etc.

The SecurActive NSS product line brings together 5 different solutions for network owners and administrators so that they can respond to effective network monitoring requirements regardless of network size.

NSS-10: Behaviour analysis of small-sized LAN networks

The SecurActive NSS-10 appliance is ideal for small-sized companies, for remote sites or for audit purposes.

SecurActive NSS-10 appliance: major advantages

- **A SIMPLE AND COMPLETE SOLUTION**

SecurActive NSS-10 was designed and produced to include the following features: network view, performance view, security view, web view, alerts and reports.

Benefits:

- No unforeseen or hidden costs
- Simplicity of integration and no-fuss operation
- Assured efficiency and streamlining of its different features

- **A FULLY INTUITIVE ADMINISTRATION SET-UP**

SecurActive NSS-10 appliance was designed for any user to go up from general information (synthesis) to a more detailed perspective in a simple and intuitive manner. The numerous wizard tools that are available facilitate the immediate and full use of the NSS-10 solution.

Benefits

- Acquisition of simplified competencies
- No added requirement for other resources to support the solution's administration
- Self-training for team users
- Ease of use by all authorised operators
- Reduced time dedicated to network administration

- **PASSIVE POSITIONING ON THE NETWORK**

SecurActive NSS-10 can be positioned on the network via a port mirroring using your own switch or can be built in via a TAP switch. The totality of your network traffic is duplicated and then transmitted to SecurActive NSS-10 to be analysed.

Benefits

- Transparency mode
- Non-intrusive integration
- No supplementary traffic generated
- No network disruption or disturbance during installation of SecurActive NSS-10.

- **NETWORK AND SECURITY PERSONALISED ALERTS**

SecurActive NSS-10 can be configured to accommodate a company's unique network alerts and security measures based on its operations, its requirements, and its IT's code of ethics. The alerts are uploaded through SecurActive's interface and/or transmitted by e-mail to administrators.

Benefits

- Possibility of supervision mode while using SecurActive NSS-10
- Significant decrease in attack risks
- Immediate resolution of network incidents and security breaches as soon as they occur.

- **CONFIGURATION ADAPTED TO NETWORK REQUIREMENTS**

SecurActive NSS-10 can also be configured so that it is adapted to meet your network's unique requirements for both infrastructure (zones and sites) and service definition requirements (identification of services and priority applications).

Benefits

- Easy and quick grasp of your network's functions and operations
- More rapid and efficient analysis of your network's activity

SecurActive NSS-10 appliance integrates the following standard functionalities:

Network Display

- Changes in observed time intervals (2 min / 2 h / 2 d / last month)
- Global traffic distribution (by IP protocol volumes, service volumes)
- Exchanged traffic by zone (volumes exchanged by zone)
- Matrix of volumes exchanged by zone
- Distribution of IP protocols
- Volume of traffic exchanged by host
- Active sessions
- Uncategorised flows
- Direct access to an IP address
- Historical records of network alerts
- Bandwidth by protocols
- Bandwidth by applicable service category
- Bandwidth for traffic < than 5%
- Bandwidth for traffic > than 5%
- Monitoring filters on IP source, destination, hours
- Alerts by network threshold limits

Security Display

- Incidents by category
- Incidents by signature
- TOP list of attackers
- TOP list of targeted hosts
- Historical records of security alerts
- Incidents by alert level

Web Display

Consultation by:

- web site
- family
- category
- zone

- source
- Export in CSV file

Response Time Management

- Measurement of both application and network latency periods
- Identification of network deteriorations

Configuration

- Configuration of the context (zone and services)
- Configuration of upstream network alerts (triggering of threshold limits)
- Configuration of upstream security alerts
- 5 levels of alerts from 1 to 5 (critical to informative)
- Management of users (access to the administrator or user box, creation of group profiles)

Reports

- Historisation of reports
- Generation of reports via assistant launch
- Generation of standard reports
- Generation of personalised reports
- Planning for the generation and transmission of reports
- Push via e-mail
- Generation of reports in HTML
- Reading of reports through Firefox or Internet Explorer

Expertise

- Generation of frame capture files
- Automatic triggering of the capture/ parameter set-up through a wizard
- Capture of up to a maximum of 10,000 frames per capture
- Stocking of local file captures
- File recovery for reading in PCAP format

Services

- Client Support DHCP
- DNS resolution support
- SMTP support
- Configuration of working hours
- NTP support
- Consideration of HTTP proxy
- Possibility of time freeze
- Automatic updates from URL classifications and security

Logging/Monitoring

- Real time monitoring of the appliance's parameters
- Secured access via login/password
- Notification by e-mail

Management

- Access to the administration of the NSS-10 solution in either WEB HTTP or HTTPS
- Two access levels: administrator or user
- Access to manage the appliance via the administration port using a Web browser
- Console port access series interface
- Access to support via remote maintenance service in cipher mode
- Access log of the appliance

Specifications and performance

- 2 listening interfaces 10/100/1000 base T copper
- 1 administration port interface 10/100/1000 base T copper
- Connectivity of the administration port via a "port mirroring" or a TAP
- Over 9,000 supported security signatures
- Support for OLFEQ categories in URL consultation

Hardware specifications

- Ethernet interfaces 10/100/1000 LAN (3 Giga Ethernet port RJ45 copper)
- HDD (Hard disk) HDD 80 GB
- Serial port (1 console port - RS232)
- Power: 60 W external power supply
- Not Rackable: Remote probe
- Dimensions: 264 x 214 x 45 mm
- Certifications: CE FCC Class A
- Weight: 2.23 Kg

SecurActive NSS-10 illustrated photos

- Front view of SecurActive NSS-10



- Back view of SecurActive NSS-10



Head Office
5 bis rue Rochechouart
75 009 Paris - France
T. +33 1 78 09 07 00
F. +33 1 78 09 07 01
www.securactive.net

About SecurActive

SecurActive is the European leader in network surveillance and security systems. Based in Paris, it distributes its SecurActive NSS product line in France and in western Europe through a network of certified partners. Additional information is available on the company's web site at www.securactive.net